

Minimum Standards Reservepilots 7/2003

Manufactures	Pilot Chutes	KG minimum	LB minimum	compression to a level of
Altico	Dolphin Pilot	9.1	20	1 inch
Chute Shop	Vortex II	14	30,8	1 inch
	Vulcan Balloon	13.6	30	1 inch
Jump Shack	Racer Pilot	9.1	20	1 inch
MarS	PV-028 (since year of manufacture 1999) PV - 031	10	22	1 inch
		4	8,8	50 mm
Mirage Systems	Mirage Reserve Pilot Chute Spring p/nRP001-36F	9.1	20	1 inch
National Parachute Ind., Inc.	Magnum 357S (shorter spring, 22 inch length, also with 36" canopy) Magnum 44 (long spring, 28 inch length with 40" canopy)	9.1-10 at manufacture	20-22 at manufacture	1 inch
		Minimum6.8	Minimum15	
P.I.S.A.	"Balloon" type with solid 0-3 CFM fabric , no mesh	13.6	30	3 cm
Parachutes de France	Quick Ref.20051002 *	12	26.4	1 inch
	Quick3	12	26.4	1 inch
	Quick 3.1	12	26.4	1 inch
Paratec	Balloon (Vector)	13.6	30	1 inch
Relative Workshop	Balloon	13.6	30	1 inch
Relative Workshop Vector1**	Vector1 Reserve Pilot Chute Spring *	9.1	20	1 inch
Rigging Innovations Please note that the Magnums are not the same as National's	Skyhook P/N2233-()	8.2	18	1 inch
	Stealth reserve PC P/N 2237-(1)	8.2	18	1 inch
	44 Magnum reserve PC P/N 2235-(3)	8.2	18	1 inch
	357 Magnum main PC P/N 2239-(2)	8.2	18	1 inch
Strong Enterprises	Grabber	8.2	18	1 inch
Sun Path	Javelin Reserve pilot	new spring is 8,7 to 9,1	new spring is 19 to 20	1 inch
Thomas Sport: Teardrop 1 pin Teardrop 2 pin Chaser Zerox**	1 pin reserve pilot chute	8.2	18	1 inch
	2 pin reserve pilot chute	8.2	18	1 inch
	2 pin reserve pilot chute	8.2	18	1 inch
	Zerox reserve pilot chute	13.6	30	1 inch

*not compatible with CYPRES

**Balloon pilot is mandatory with CYPRES